

EXPERIENCE A NEW STANDARD FOR LINEAR LIGHTING



Adding another chapter in US LED's history of engineering design, the LinearStar® outdoor LED sign accent lighting is the embodiment of elegance and efficiency. More than just a light, LinearStar's minimalist presence seamlessly integrates into the overall architecture and utilizes proprietary optics to project light evenly across the targeted area.

PRODUCT FEATURES

- LinearStar can be scaled to illuminate any length of flat or embossed surfaces with available 1' and 4' sections.
- Individual units can be serviced or replaced without disturbing adjacent mounted sections.
- Proprietary refractive optics allow close proximity placement to the signage or wall application.
- Adjustable swivel head for precise control of illumination.
- Full cut-off operation with 18°, 22°, and 27° preset angles.





PRODUCT PERFORMANCE SUMMARY

LUMEN OUTPUT	Up To 1,350L (Per Section)
EFFICACY	Up To 92 LPW (Per Section)
CRI	≥ 80 CRI
AVAILABLE CCT	5000K

PRODUCT APPLICATIONS

- Signage Lighting
- Wall Washing



THE ONLY LIMIT IS YOUR IMAGINATION

LinearStar® outdoor sign accent lighting will allow potential customers to find you more easily and create a dynamic first impression. Its durable construction is designed to withstand the environmental elements all while showing your brand in the best light possible. With your choice of lengths, an adjustable swivel head, and its proprietary optics, you can transform your exterior space with the perfect amount of illumination.

	1 FT. UNIT	4 FT. UNIT
DIMENSIONS	12 in. x 3 in. x 2 in.	48 in. x 3 in. x 2 in.
NET WEIGHT	0.3 lbs. (0.14kg)	1.20 lbs. (0.54kg)
ENVIRONMENT RATING	Wet Locations	Wet Locations
INPUT VOLTAGE	120-277V	120-277V
L70 CALCULATED LIFE	≥163,000 Hours	≥163,000 Hours
L85 CALCULATED LIFE	≥82,000 Hours	≥82,000 Hours
OPERATING TEMPERATURE	40°C to +45°C (-40°F to +113°F)	40°C to +45°C (-40°F to +113°F)

USLED
Always the Right Choice!